

Replacement pump GTK 5200 without float switch



Article information

Item no.: 680708
 GTIN: 4026092082034
 Price group: 90

Description

Replacement pump GTK 5200 without float switch, for pumping station, wet installation

Variant

Pump control:

Control unit

General characteristics

Type of wastewater:

without sewage

Dimensions

Net weight:

57 kg

Gross weight:

59 kg

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Pumping device

Pump:

GTK 5200

Weight, pump:

56 kg

Connection type:

Direct connection

Operating voltage:

400 V

Mains frequency:

50 Hz

Protection class:

I

Insulation class:

H

Cos phi - power factor:

0,85

Protection class (pump):

IP 68

Max. temperature (permanent) of conveyed material:

40 °C

Max. pumping height:

31,6 m

Speed:

2840 U/min

Power P1:

5,2 kW

Power P2:

4,4 kW

Operating mode:

S3 - 30 %

Type of pump connection cable:	H07RN8-F PLU 10G 1.5 mm ²
Length of mains cable for pump:	10 m
Rated current:	8,7 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V