

Replacement pump GTK 5200 without float switch



Article information

Item no.: 680708
 GTIN: 4026092082034
 Price group: 90

Description

Replacement pump GTK 5200 without float switch, for pumping station, wet installation

Variant	
Pump control:	Control unit
General characteristics	
Type of wastewater:	without sewage
Dimensions	
Net weight:	57 kg
Gross weight:	59 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	GTK 5200
Weight, pump:	56 kg
Connection type:	Direct connection
Operating voltage:	400 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	H
Cos phi - power factor:	0,85
Protection class (pump):	IP 68
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping height:	31,6 m
Speed:	2840 U/min
Power P1:	5,2 kW
Power P2:	4,4 kW
Operating mode:	S3 - 30 %

Type of pump connection cable:
Type of fuse required (pump):
Length of mains cable for pump:
Rated current:

H07RN8-F PLU 10G 1.5 mm²
Fuse protection through control unit 400 V
10 m
8,7 A

Control
Operating voltage:
Connection type:

400 V
Direct connection