

Replacement pump GTF 500 with float switch, Aqualift S size 3



Article information

Item no.: 680828
GTIN: 4026092085547
Price group: 90

Description

Replacement pump GTF 500 , assembled ready to plug-in, with float switch, for faecal-free wastewater.

Dimensions

| | |
|----------------------|---------|
| Net weight: | 5,95 kg |
| Gross weight: | 6,3 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Pumping device

| | |
|--|--------------------------------|
| Pump: | GTF 500 |
| Operating voltage: | 230 V |
| Mains frequency: | 50 Hz |
| Protection class: | I |
| Protection class (pump): | IP 68 |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Max. pumping height: | 8 m |
| Speed: | 2800 U/min |
| Power P1: | 0,6 kW |
| Power P2: | 0,36 kW |
| Operating mode: | S1 |
| Type of pump connection cable: | H07RN-F 3G 1.5 mm ² |
| Type of fuse required (pump): | C 16 A |
| Length of mains cable for pump: | 5 m |
| Rated current: | 2,7 A |

Control

| | |
|--------------------|-------|
| Operating voltage: | 230 V |
|--------------------|-------|