

Replacement pump GTF 1250 without float switch, 10 m



Article information

Item no.: 680966 GTIN: 4026092095416

Price group: 90

Description

Replacement pump with float switch for wastewater containing faecal matter.

General characteristics

Type of wastewater: without sewage

Dimensions

Net weight:11 kgGross weight:11 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Pumping device

Pump: GTF 1250

Connection type: Schuko (earthed contact) 2-pin

Operating voltage: 230 V Mains frequency: 50 Hz Protection class (pump): IP 68 (3m) Max. temperature (permanent) of conveyed $40\,^{\circ}\text{C}$

material:

Max. pumping height: 11 m

Speed: 2700 U/min
Power P1: 1,3 kW
Power P2: 0,8 kW
Operating mode: S1

Type of pump connection cable: H07RN-F 3G 1.5 mm² Impeller type: Multi-vane impeller

Type of fuse required (pump): C 16 A
Length of mains cable for pump: 10 m
Rated current: 5,4 A

Control

Operating voltage: 230 V



\sim				
I,U	വവ	ctior	1 T\/I	വ
\cup	шь	G HUI	1 LVI	JE.

Schuko (earthed contact) 2-pin