

## Replacement pump GTF 1250 without float switch, 10 m



### Article information

Item no.: 680966  
 GTIN: 4026092095416  
 Price group: 90

### Description

Replacement pump with float switch for wastewater containing faecal matter.

#### General characteristics

Type of wastewater: without sewage

#### Dimensions

Net weight: 11 kg  
 Gross weight: 11 kg  
 Packaging dimension: width  
 Packaging dimension: height  
 Packaging dimension: length

#### Pumping device

Pump control: GTF 1250  
 Connection type: Schuko (earthed contact) 2-pin  
 Rated current: 5,4 A  
 Length of mains cable for pump: 10 m  
 Protection class control unit: IP 68 (3m)  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping height: 11 m  
 Speed: 2700 U/min  
 Power P1: 1,3 kW  
 Power P2: 0,8 kW  
 Operating mode: S1  
 Type of fuse required (electrical protection): C 16 A  
 Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>  
 Impeller type: Multi-vane impeller

#### Control

Mains frequency: 50 Hz  
 Operating voltage: 230 V  
 Connection type: Schuko (earthed contact) 2-pin