
Backwater valve Staufix DN 90, Floor slab, tileable, Type 2 R





Article information

Item no.: 730090.10XR
GTIN: 4026092076330
Price group: 10

Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant	
Stainless steel flap as rat protection:	yes
Emergency closure:	yes
Mechanical backwater flaps:	2
General characteristics	
Colour:	black
Standard:	EN 13564
Nominal size (DN):	90
Outer diameter (OD):	90 mm
Type of wastewater:	without sewage
Installation situation:	floor slab installation
Delivery state:	Installation-ready (connection parts must be connected on site)
Backwater protection:	Type 2
Dimensions	
Net weight:	5,95 kg

Gross weight:	8,55 kg
Groundwater resistant from lower edge of base section:	3 mm
Cutout dimension, width:	750 mm
Cutout dimension, length:	750 mm
Vertical drop between inlet and outlet:	8 mm
Installation depth:	287 - 410 mm
Vertical adjustment:	vertically adjustable upper section
Width:	444 mm
Length:	444 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Coverage features

Type of cover:	tileable cover plate
Cover material:	Polymer
Width of cover:	366 mm
Length of cover:	366 mm
Cover locking:	Lock & Lift
Load class:	K 3 (EN 1253-1)
Tightness:	surface water resistant
Max. flooring height:	16 mm