

## Backwater valve Staufix DN 125, exposed, Type 2 R



### Article information

Item no.: 730125R  
 GTIN: 4026092076460  
 Price group: 10

### Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

### Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

#### Variant

Stainless steel flap as rat protection:	yes
Emergency closure:	yes
Mechanical backwater flaps:	2

#### General characteristics

Colour:	black
Standard:	EN 13564
Nominal size (DN):	125
Outer diameter (OD):	125 mm
Type of wastewater:	without sewage
Installation situation:	exposed drainage pipe
Delivery state:	installation-ready
Backwater protection:	Type 2

#### Dimensions

Net weight:	3,2 kg
Gross weight:	5,8 kg
Vertical drop between inlet and outlet:	8 mm
Width:	214 mm
Height:	306 mm
Length:	515 mm
Packaging dimension:	width
Packaging dimension:	height

Packaging dimension:

length

Coverage features

Type of cover:

Lockable cover

Adjustment range:

One-handed closure