
IK KESSEL

Controlfix clean out DN 150, Floor slab, black





Article information

Item no.: 80150S GTIN: 4026092004098 Price group: 30

Advantages

- Simple conversion to Staufix SWA
- Fast, simple and toolless maintenance
- Quick and toolless access for cleaning

Description

The Premium clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work. Thanks to the modular KESSEL system, existing systems can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

General characteristics Colour: Nominal size (DN): Outer diameter (OD): Type of wastewater: Installation situation: Delivery state:	black 150 160 mm for wastewater with and without sewage floor slab installation Installation-ready (connection parts must be connected on site)
Dimensions Net weight: Gross weight: Groundwater resistant from lower edge of base	14 kg 17,32 kg 3000 mm
section: Cutout dimension, width: Cutout dimension, length: Vertical drop between inlet and outlet: Installation depth: Type of height adjustability: Length:	750 mm 750 mm 9 mm 516 - 669 mm vertically adjustable upper section 486 mm



Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Locking: Load class: Tightness: 590 mm length width height

including spigot and socket

Cover plate Polymer black 366 mm 366 mm Lock & Lift L 15 (EN 1253-1) surface water resistant