

## Pumping station Aquapump Medium Duo, STZ 1000, 1300-1750 mm, A



### Article information

Item no.: 826721A  
 GTIN: 4026092077658  
 Price group: 60

### Advantages

- height-adjustable upper section
- Preconfigured in the factory
- LW 600 chamber system suitable for underground installation

### Description

The pumping station with sewage wastewater is suitable for underground installation and is equipped with a non-return flap for the pressure pipe. The PE-LLD tank is resistant to aggressive media and can be delivered with load class A, B or D covers. The pump with macerator ensures maximum operating reliability. The components are pre-assembled for final assembly on site. Including openings for ventilation and cable duct.

#### Variant

|   |                  |
|---|------------------|
| Type of system:                         | duo pump         |
| Passage seal for conduit pipe (DN):     | 100              |
| Access steps:                           | no               |
| Passage seal for ventilation pipe (DN): | 100              |
| Installation:                           | Wet installation |
| Pump control:                           | Control unit     |
| Backflow preventer:                     | integrated       |
| Pressure pipe connection:               | horizontal       |
| Chamber system:                         | LW 600           |

#### General characteristics

|                         |  |
|-------------------------|--|
| Standard:               | EN 12050-1                             |
| Type of wastewater:     | for wastewater with and without sewage |
| Installation situation: | underground installation               |
| System type:            | Duo                                    |
| ATEX:                   | no                                     |

#### Dimensions

|               |        |
|---------------|--------|
| Net weight:   | 127 kg |
| Gross weight: | 139 kg |

|  |                                |
|--|--------------------------------|
| Groundwater resistant from lower edge of base section: | 2500 mm                        |
| Diameter:  | 809 mm                         |
| Clear width (LW):                                      | 600 mm                         |
| Installation depth:                                    | 1300 - 1750 mm                 |
| Length:  | 1000 mm                        |
| Width:   | 806 mm                         |
| Packaging dimension:                                   | length                         |
| Packaging dimension:                                   | width                          |
| Packaging dimension:                                   | height                         |
| Tank/drain body  |                                |
| Pressure pipe connection (DN):                         | 32                             |
| Pressure pipe connection (OD):                         | 40 mm                          |
| Connection conduit pipe (DN):                          | 100                            |
| Venting connection (DN):                               | 100                            |
| Distance from centre of outlet pipe to tank bottom:    | 894 mm                         |
| Distance pipe bottom inlet to tank bottom:             | 400 mm                         |
| Distance from centre of inlet pipe to tank bottom:     | 475 mm                         |
| Inlet nominal size (DN):                               | 150 mm                         |
| Number of inlets:                                      | 1                              |
| Clear width of tank (LW):                              | 600 mm                         |
| Pumping volume:  | 30 l                           |
| Coverage features                                      |                                |
| Type of cover:   | Round cover plate              |
| Load class:  | A 15 (EN 124)                  |
| Pumping device   |                                |
| Pump:  | STZ 1000                       |
| Number of pumps:                                       | 2                              |
| Weight, pump:  | 10 kg                          |
| Connection type:                                       | Schuko (earthed contact) 2-pin |
| Rated current:   | 5,2 A                          |
| Length of mains cable for pump:                        | 10 m                           |
| Protection class:                                      | I                              |
| Insulation class:                                      | F                              |
| Protection class (pump):                               | IP 68 (3m)                     |
| Max. temperature (permanent) of conveyed material:     | 40 °C                          |
| Max. pumping capacity:                                 | 11,5 m <sup>3</sup> /h         |
| Max. pumping height:                                   | 10 m                           |
| Speed:   | 2800 U/min                     |
| Power P1:  | 1,2 kW                         |
| Power P2:  | 0,69 kW                        |
| Operating mode:  | S3 - 50 %                      |
| Type of fuse required (electrical protection):         | C 16 A                         |
| Impeller type:   | Macerator                      |

|  |                                |
|--|--------------------------------|
| Control  |                                |
| Control unit:                                  | Comfort                        |
| Control unit function:                         | With alarm message             |
| Motor protection switch:                       | yes                            |
| Alarm sensor:                                  | optical probe                  |
| Level measurement instrument:                  | Submersible pressure switch    |
| Type of level measurement:                     | pneumatic                      |
| Protection class control unit:                 | IP 54                          |
| Mains frequency:                               | 50 Hz                          |
| Operating voltage:                             | 230 V                          |
| Connection type:                               | Schuko (earthed contact) 2-pin |
| Potential-free contact:                        | yes                            |
| GSM interface:                                 | yes                            |
| USB interface:                                 | yes                            |
| Log book function:                             | yes                            |
| Multi-line display:                            | yes                            |
| Battery buffering:                             | yes                            |
| Self-diagnosis system (SDS):                   | yes                            |
| Warning equipment version:                     | acoustic and optical signal    |
| Rated current:                                 | 5,2 A                          |
| Type of fuse required (electrical protection): | C 16 A                         |