

Yard drain System 400, DN 150, D, 730 - 1080 mm



Article information

Item no.: 851152D GTIN: 4026092004425

Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

Variant

System: 400
Heating: without
Contents of sludge trap: yes
Sealing water height: 100 mm
Discharge rate (l/s) with 20 mm threshold: 4,5

General characteristics

Colour: black
Standard: EN 752
Nominal size (DN): 150
Outer diameter (OD): 160 mm
Odour trap: included

Dimensions

Net weight:50 kgGross weight:50 kgGroundwater resistant from lower edge of base500 mm

section:

Cutout dimension, width: 535 mm
Cutout dimension, length: 585 mm
Min. insertion depth: 55 mm

Installation depth: 730 - 1080 mm

Type of height adjustability: vertically adjustable upper section

Packaging dimension: length Packaging dimension: width Packaging dimension: height



Tank/drain body

Number of outlets:

Material of drain body: Polymer Socket version: lateral

Coverage features

Type of cover: Round slotted cover

Cover material: Grey iron
Colour of cover: black
Width of cover: 450 mm
Length of cover: 450 mm
Surface: EDM

Load class: D 400 (EN 124)

Rim width: 450 mm
Rim length: 450 mm
Shape of upper section: square
Contents of sludge trap: yes