

Sealing set for cable duct 230V for sealing on the building side



Article information

Item no.: 85401
GTIN: 4026092102954
Price group: 60

Description

Consisting of the Quadro-Sicura Quick/H single-pipe house entry system with injection system for use in all standard wall types with a wall thickness of 200-550 mm.

Including DN100 sealing insert for feed-through and waterproofing layer of all required cables for boiler system solutions with 230V mains voltage.

Technical data "Doyma Quadro Secura Quick/H"

- Dimensions: sleeve tube L= 760mm, D= 250mm
- Dimensions: Sealing flange D= 250mm
- Use in the most common wall types with waterproofing layer according to DIN 18533 W2.1-E (black tank) or waterproof concrete core drilling (white tank)
- for wall thicknesses 200 - 550 mm
- For installation in casing pipe / core drill hole DN 150 from 149 mm to 153 mm
- Connection option for rigid or flexible DN 110 casing pipes
- with injection system, for gas-tight and pressurised water-tight waterproofing layers of pipes and cables, with integrated sleeve pipe to accommodate boiler sealing insert in D100.
- Waterproofing layer and fixing by means of resin injection
- With integrated run-off stop for the expansion resin to be applied
- Tightening the outer seal with integrated torque control using special self-shearing nuts
- Also suitable for standard hollow bricks
- with tested radon tightness

Technical data sealing insert

- Dimensions: D100 (for 99-104mm), L= 65mm - 7 cable openings
- Unused openings closed with blind plugs
- Tightness up to 0.5 bar water pressure

Dimensions

Net weight: 6,61 kg
Gross weight: 6,31 kg
Packaging dimension: length

Packaging dimension:
Packaging dimension:

width
height