


Upper Section LW 600 Begu, height-adjustable 79 - 579 mm





Article information

Item no.: 860154 GTIN: 4026092102503 Price group: 60

Description

Upper section with clamping ring suitable for chamber systems LW 1000/800/600 for covers resistant to surface water, class A/B or D, with Lock & Lift, continuously height-adjustable by 514 mm (Comfort and engineering chamber system) or 400 mm (standard chamber system).

If installed in roads, parking areas and comparable hard-surfaced traffic areas for trucks (Class D), the upper section must be underlaid on site with a reinforced supporting slab made of concrete. A standard formwork and reinforcement drawing can be provided.

Access steps (art. no. 860109) must be installed if the allowable difference between the top of the chamber cover and the first step is exceeded.

DimensionsNet weight:16,39 kgGross weight:16,39 kgDiameter:850 mmAdjustment range:79 - 579Height:659 mmPackaging dimension:lengthPackaging dimension:widthDaskaging dimension:beight	Minimum insertion depth:	80 mm (Comfort and engineering chamber system) or 94 mm (standard chamber system and cisterns).
Gross weight:16,39 kgDiameter:850 mmAdjustment range:79 - 579Height:659 mmPackaging dimension:lengthPackaging dimension:width	Dimensions	
Diameter:850 mmAdjustment range:79 - 579Height:659 mmPackaging dimension:lengthPackaging dimension:width	Net weight:	16,39 kg
Adjustment range:79 - 579Height:659 mmPackaging dimension:lengthPackaging dimension:width	Gross weight:	16,39 kg
Height:659 mmPackaging dimension:lengthPackaging dimension:width	Diameter:	850 mm
Packaging dimension:lengthPackaging dimension:width	Adjustment range:	79 - 579
Packaging dimension: width	Height:	659 mm
	Packaging dimension:	length
Dealersing dimensions beight	Packaging dimension:	width
Packaying unnension. neight	Packaging dimension:	height



Coverage features Cover material: Colour of cover:

PP black