Chamber module LW 1000 floor slab Access LW 600, 3880-4129 mm, Class D



Article information

Item no.: 8740085
GTIN: 4026092066003
Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

Variant	
Note on installation depth:	note maximum installation depth 5000 mm in combination with technical module
General characteristics	
Colour:	black
Material:	PE-HD
Standard:	EN 13598-2
Installation situation:	underground installation
Delivery state:	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Inlet max. scoring (DN):	Z-42.1-527
Dimensions	
Net weight:	268 kg
Gross weight:	301 kg
Groundwater resistant from lower edge of base section:	3000 mm
Installation depth:	3880 - 4129 mm
Vertical adjustment:	vertically adjustable upper section
Width:	1200 mm

Length:	1200 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body

Number of inlets:	150 mm
Clear width of tank (LW):	1000 mm
Clear width of entry (LW):	600 mm

Coverage features

Type of cover:	Round cover plate
Cover material:	Grey iron
Colour of cover:	black
Width of cover:	659 mm
Height of cover:	122 mm
Length of cover:	659 mm
Surface:	Grey iron
Cover locking:	locked
Load class:	D 400 (EN 124)
Tightness:	surface water resistant