
Chamber module LW 1000 floor slab Access LW 800, 2375-2624 mm, Class K 3





Article information

Item no.: 8740130
GTIN: 4026092071663
Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

General characteristics	
Colour:	black
Material:	PE-HD
Standard:	EN 13598-2
Installation situation:	underground installation
Delivery state:	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Inlet max. scoring (DN):	Z-42.1-527

Dimensions	
Net weight:	183,67 kg
Gross weight:	222,31 kg
Groundwater resistant from lower edge of base section:	3000 mm

Installation depth:	2375 - 2624 mm
Vertical adjustment:	vertically adjustable upper section
Width:	1200 mm
Length:	1200 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body

Number of inlets:	150 mm
Clear width of tank (LW):	1000 mm
Clear width of entry (LW):	800 mm

Coverage features

Type of cover:	Round cover plate
Cover material:	Stainless steel
Width of cover:	960 mm
Height of cover:	19 mm
Length of cover:	960 mm
Surface:	anti-slip
Cover locking:	screwed
Load class:	K 3 (EN 1253-1)
Tightness:	surface water resistant