

Sampling chamber d: 450 mm, DN 100, Class D



Article information

Item no.: 915881D
 GTIN: 4026092055410
 Price group: 60

Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

General characteristics

Colour: black
 Material: PE

Dimensions

Net weight: 47 kg
 Gross weight: 53 kg
 Vertical drop between inlet and outlet: 160 mm
 Installation depth: 0 mm
 Vertical adjustment: vertically adjustable upper section
 Length: 730 mm
 Packaging dimension: width
 Packaging dimension: height
 Packaging dimension: length

Tank/drain body

Distance pipe bottom inlet to tank bottom: 205 mm
 Outlet nominal size (OD): 110 mm
 Outlet nominal size (DN): 100
 Inlet nominal size (DN): 110 mm
 Inlet nominal size (DN): 100
 Clear width of tank (LW): 450 mm

Coverage features

Type of cover: Cover plate
 Cover material: Grey iron
 Colour of cover: black

Load class:
Tightness:

D 400 (EN 124)
odour-tight and surface water resistant