

## Sampling chamber DN 250, Load class A



### Article information

Item no.: 915884A  
 GTIN: 4026092086322  
 Price group: 60

### Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Upper section made of polymer for continuous adjustable height and level adjustment.

|   |                |
|---|----------------|
| Chamber system:   | LW 450         |
| Flow direction:   | straight       |
| Inlet installation depth:<br>(can be shortened to 450 mm by sawing) | 950 to 1300 mm |

#### General characteristics

|                      |        |
|----------------------|--------|
| Material:            | PE     |
| Nominal size (DN):   | 250    |
| Outer diameter (OD): | 260 mm |

#### Dimensions

|   |               |
|---|---------------|
| Net weight:                             | 15 kg         |
| Gross weight:                           | 15 kg         |
| Vertical drop between inlet and outlet: | 160 mm        |
| Installation depth:                     | 950 - 1300 mm |
| Packaging dimension:                    | length        |
| Packaging dimension:                    | width         |
| Packaging dimension:                    | height        |

#### Coverage features

|                 |   |
|-----------------|---|
| Type of cover:  | Cover plate                             |
| Cover material: | Grey iron                               |
| Load class:     | A 15 (EN 124)                           |
| Tightness:      | odour-tight and surface water resistant |