

## Grease separator EasyClean free NS 3, Standard



## **Article information**

Item no.: 93003.01 GTIN: 4026092060889 Price group: 60

## **Advantages**

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

## Description

Variant

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	
Disposal variant:	Standard
Protection class motor:	no
Sludge bucket:	no
Nominal size (NS):	3
SonicControl:	no
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
Dimensions Net weight: Gross weight: Set-up area, length: Set-up area, width: Set-up area, height:	87 kg 117 kg 1736 mm 674 mm 1434 mm



Required access area, length:	1500 mm
Required access area, width:	674 mm
Required access area, height:	1434 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
5 5	5
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	985 mm
Distance pipe bottom inlet to tank bottom:	1055 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (DN):	110 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	300 l
Total volume:	600 l
Hose:	300 l
Storage quantity of light liquid:	120 l
Control	
Control unit:	