

Grease separator EasyClean free NS 3, Standard, Refill in., SonicControl



Article information

Item no.: 93003.12
GTIN: 4026092063231
Price group: 60

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:	Standard
Protection class motor:	no
Sludge bucket:	no
Nominal size (NS):	3
SonicControl:	yes
Refill inlet in accordance with DIN 1988:	yes
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3

General characteristics

Material:	PE
Installation situation:	free-standing installation
Delivery state:	Installation-ready (connection parts must be connected on site)

Dimensions

Net weight:	99 kg
Gross weight:	129 kg
Set-up area, width:	674 mm
Set-up area, height:	1434 mm

Set-up area, length:	1736 mm
Required access area, width:	674 mm
Required access area, height:	1434 mm
Required access area, length:	1500 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body

Distance pipe bottom outlet to tank bottom:	985 mm
Distance pipe bottom inlet to tank bottom:	1055 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100
Inlet nominal size (DN):	110 mm
Inlet nominal size (DN):	100
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight

Wastewater contents

Separator contents:	300 l
Total volume:	600 l
Hose:	300 l
Storage quantity of light liquid:	120 l

Control

Max. permissible switching frequency:	no
---------------------------------------	----