

## Grease separator EasyClean free NS 3, Standard, Inspection window, SC



### Article information

Item no.: 93003.22  
 GTIN: 4026092063330  
 Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

#### Variant

|   |                          |
|---|--------------------------|
| Disposal variant:                         | Standard                 |
| Protection class motor:                   | no                       |
| Sludge bucket:                            | yes                      |
| Nominal size (NS):                        | 3                        |
| SonicControl:                             | yes                      |
| Refill inlet in accordance with DIN 1988: | no                       |
| Type of disposal:                         | manual with suction hose |
| Load-bearing capacity (DIN 19901):        | F3                       |

#### General characteristics

|                         |   |
|-------------------------|---|
| Material:               | PE  |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |

#### Dimensions

|                      |          |
|----------------------|----------|
| Net weight:          | 98,5 kg  |
| Gross weight:        | 128,5 kg |
| Set-up area, length: | 1736 mm  |
| Set-up area, width:  | 674 mm   |

|                               |         |
|-------------------------------|---------|
| Set-up area, height:          | 1434 mm |
| Required access area, length: | 1500 mm |
| Required access area, width:  | 674 mm  |
| Required access area, height: | 1434 mm |
| Packaging dimension:          | length  |
| Packaging dimension:          | width   |
| Packaging dimension:          | height  |

#### Tank/drain body

|   |   |
|---|---|
| Distance pipe bottom outlet to tank bottom: | 985 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1055 mm   |
| Outlet nominal size (OD):                   | 110 mm  |
| Outlet nominal size (DN):                   | 100 mm  |
| Inlet nominal size (DN):                    | 110 mm  |
| Inlet nominal size (DN):                    | 100 mm  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

#### Coverage features

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Cover locking:   | Quick-release closure |
| Tightness:       | odour-tight           |

#### Wastewater contents

|                                   |       |
|-----------------------------------|-------|
| Separator contents:               | 300 l |
| Total volume:                     | 600 l |
| Hose:                             | 300 l |
| Storage quantity of light liquid: | 120 l |

#### Control

|               |    |
|---------------|----|
| Control unit: | no |
|---------------|----|