

Grease separator EasyClean free NS 3, Standard, Ref. in., Insp. Win., SC



Article information

Item no.: 93003.32 GTIN: 4026092063439 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	
Disposal variant:	Standard
Protection class motor:	no
Sludge bucket:	yes
Nominal size (NS):	3
SonicControl:	yes
Refill inlet in accordance with DIN 1988:	yes
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
Dimensions	
Net weight:	99,5 kg
Gross weight:	129,5 kg
Set-up area, length:	1736 mm
Set-up area, width:	674 mm



Set-up area, height: Required access area, length: Required access area, width: Required access area, height: Packaging dimension: Packaging dimension:	1434 mm 1500 mm 674 mm 1434 mm length width height
Tank/drain body Distance pipe bottom outlet to tank bottom: Distance pipe bottom inlet to tank bottom: Outlet nominal size (OD): Outlet nominal size (DN): Inlet nominal size (DN): Inlet nominal size (DN): Connection inlet/outlet sockets:	985 mm 1055 mm 110 mm 100 mm 110 mm 100 mm PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features Type of cover: Cover material: Colour of cover: Cover locking: Tightness:	Cover Polymer violet Quick-release closure odour-tight
Wastewater contents Separator contents: Total volume: Hose: Storage quantity of light liquid:	300 l 600 l 300 l 120 l
Control Control unit:	по