

Grease separat. EasyClean Modular free, NS 4, round, Direct disposal







Article information

Item no.: 93004.00/D1-R GTIN: 4026092108284

Price group: 60

Advantages

- Ideal where access is tight
- can be divided into 3 parts for insertion, for an insertion opening of max. 66 cm
- Direct disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. 20 year polyethylene warranty.

Variant

Chamber system: two-piece chamber

Disposal variant: Direct Nominal size (NS): 4

Disposal system: Disposal connection

Type of disposal: manual

General characteristics

Material: PE Standard: FN

Standard: EN 1825
Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle

connection



Dimensions

Net weight: 100 kg Gross weight: 120 kg Set-up area, height: 1620 mm Required access area, length: 1400 mm Required access area, width: 1300 mm Required access area, height: 790 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Outlet nominal size (DN): 100
Inlet nominal size (DN): 100

Coverage features

Type of cover: Cover

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 560 l
Total volume: 980 l
Contents of sludge trap: 420 l
Storage quantity of grease: 160 l