

Grease separator EasyClean free NS 4, Standard, Refill inlet



Article information

Item no.: 93004.11 GTIN: 4026092063194 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

Variant

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

| Variant | |
|---|--|
| Disposal variant: | Standard |
| Protection class motor: | no |
| Sludge bucket: | no |
| Nominal size (NS): | 4 |
| SonicControl: | no |
| Refill inlet in accordance with DIN 1988: | yes |
| Type of disposal: | manual with suction hose |
| Load-bearing capacity (DIN 19901): | F3 |
| General characteristics Material: Installation situation: Delivery state: | PE free-standing installation Installation-ready (connection parts must be connected on site) |
| Dimensions Net weight: Gross weight: Set-up area, width: Set-up area, height: Set-up area, length: | 101 kg 131 kg 680 mm 1432 mm 2116 mm |



| Required access area, width: | 680 mm |
|---|--|
| Required access area, height: | 1432 mm |
| Required access area, length: | 1880 mm |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Packaging dimension: | length |
| | |
| Tank/drain body | |
| Distance pipe bottom outlet to tank bottom: | 985 mm |
| Distance pipe bottom inlet to tank bottom: | 1055 mm |
| Outlet nominal size (OD): | 110 mm |
| Outlet nominal size (DN): | 100 |
| Inlet nominal size (DN): | 110 mm |
| Inlet nominal size (DN): | 100 |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes |
| | in accordance with DIN 19560, PP or AS |
| Coverage features | |
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | violet |
| Cover locking: | Quick-release closure |
| Tightness: | odour-tight |
| | |
| Wastewater contents | |
| Separator contents: | 400 l |
| Total volume: | 800 l |
| Hose: | 400 l |
| Storage quantity of light liquid: | 160 l |
| Control | |
| Max. permissible switching frequency: | po |
| יימג. אפורוויפטוופ פאיונטווווט וופעטפווטץ. | no |
| | |