


Grease separator EasyClean ground NS 4, Direct, 550-950 mm, D, left





Article information

Item no.: 93004.80D-DL GTIN: 4026092094877 Price group: 60

Advantages

- Low odour and clean disposal
- Defined disposal point
- Complete emptying of the separator

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers. A direct disposal pipe socket is available for odour-reduced manual disposal. A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL. 20 year polyethylene warranty.

Variant Note on installation depth: Direction of flow: Disposal variant: Nominal size (NS): Disposal system: Type of disposal: Load-bearing capacity (DIN 19901):

General characteristics Material: Installation situation: Delivery state: Installation in the ground, frost-free depth 800 mm left Direct 4 Disposal pipe manual E4

ΡE

underground installation Installation-ready (connection parts must be connected on site)



Dimensions Net weight: Gross weight: Groundwater resistant from lower edge of base section:	130 kg 137 kg 500 mm
Diameter: Installation depth: Length:	648 mm 550 - 900 mm 1380 mm
Width: Packaging dimension:	1106 mm length
Packaging dimension: Packaging dimension:	width height
Tank/drain body Distance pipe bottom outlet to tank bottom:	1040 mm
Distance pipe bottom inlet to tank bottom:	1110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG
	pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW):	600 mm
Coverage features	
Type of cover: Cover material:	Cover plate
Colour of cover:	Grey iron black
Load class:	D 400 (EN 124)
Tightness:	odour-tight and surface water resistant
Wastewater contents	
Separator contents:	370 l
Hose:	400 l
Storage quantity of light liquid:	160 l
Sealing water height:	160 l

No

purchasable by service partner: