

Grease separator EasyClean free NS 7, Standard



Article information

Item no.: 93007.01 GTIN: 4026092060902 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant Disposal variant: Protection class motor: Sludge bucket: Nominal size (NS): SonicControl: Refill inlet in accordance with DIN 1988: Type of disposal: Load-bearing capacity (DIN 19901):	Standard no no 7 no no manual with suction hose F3
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
Dimensions Net weight: Gross weight: Set-up area, width: Set-up area, height: Set-up area, length:	152 kg 185 kg 948 mm 1653 mm 2147 mm



Required access area, width:	948 mm
Required access area, height:	1653 mm
Required access area, length:	1910 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length
	lengun
Topk/drain body	
Tank/drain body Distance pipe bottom outlet to tank bottom:	1185 mm
	1255 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	150
Outlet nominal size (DN):	
Inlet nominal size (DN):	160 mm
Inlet nominal size (DN):	
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	
Colour of cover:	Polymer violet
Cover locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	650 l
Total volume:	1350 l
	700 l
Hose:	
Storage quantity of light liquid:	280 l
Control	
	po
Max. permissible switching frequency:	ΠΟ