

## Grease separator EasyClean free NS 7, Direct, SonicControl



### Article information

Item no.: 93007.02/D  
GTIN: 4026092061534  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

#### Variant

|   |                     |
|---|---------------------|
| Disposal variant:                         | Direct              |
| Protection class motor:                   | no                  |
| Sludge bucket:                            | no                  |
| Nominal size (NS):                        | 7                   |
| SonicControl:                             | yes                 |
| Disposal system:                          | Disposal connection |
| Refill inlet in accordance with DIN 1988: | no                  |
| Type of disposal:                         | manual              |
| Load-bearing capacity (DIN 19901):        | F3                  |

#### General characteristics

|                         |   |
|-------------------------|---|
| Material:               | PE  |
| Standard:               | EN 1825   |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |
| Scope of delivery:      | Storz-B coupling R 2 1/2" for disposal vehicle connection       |

#### Dimensions

|   |   |
|---|---|
| Net weight:                                 | 195 kg  |
| Gross weight:                               | 225 kg  |
| Set-up area, width:                         | 970 mm  |
| Set-up area, height:                        | 1653 mm   |
| Set-up area, length:                        | 2147 mm   |
| Required access area, width:                | 940 mm  |
| Required access area, height:               | 1653 mm   |
| Required access area, length:               | 1910 mm   |
| Packaging dimension:                        | width   |
| Packaging dimension:                        | height  |
| Packaging dimension:                        | length  |
| Tank/drain body                             |   |
| Nominal pressure (PN):                      | 10  |
| Pressure pipe connection (DN):              | 65  |
| Pressure pipe connection (OD):              | 75 mm   |
| Distance pipe bottom outlet to tank bottom: | 1185 mm   |
| Distance pipe bottom inlet to tank bottom:  | 1255 mm   |
| Outlet nominal size (OD):                   | 160 mm  |
| Outlet nominal size (DN):                   | 150   |
| Inlet nominal size (DN):                    | 160 mm  |
| Inlet nominal size (DN):                    | 150   |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Servicing opening:                          | 420 mm  |
| Coverage features                           |   |
| Type of cover:                              | Cover   |
| Cover material:                             | Polymer   |
| Colour of cover:                            | violet  |
| Cover locking:                              | Quick-release closure   |
| Tightness:                                  | odour-tight   |
| Wastewater contents                         |   |
| Separator contents:                         | 650 l   |
| Total volume:                               | 1350 l  |
| Hose:                                       | 700 l   |
| Storage quantity of light liquid:           | 280 l   |
| Control                                     |   |
| Max. permissible switching frequency:       | no  |