

Grease separator EasyClean free NS 7, Direct, Insp. window, SonicControl



Article information

Item no.: 93007.22/D
GTIN: 4026092063651
Price group: 60

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

Variant

Disposal variant:	Direct
Protection class motor:	no
Sludge bucket:	yes
Nominal size (NS):	7
SonicControl:	yes
Disposal system:	Disposal connection
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual
Load-bearing capacity (DIN 19901):	F3

General characteristics

Material:	PE
Standard:	EN 1825
Installation situation:	free-standing installation
Delivery state:	Installation-ready (connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

Dimensions

Net weight:	161 kg
Gross weight:	194 kg
Set-up area, width:	970 mm
Set-up area, height:	1653 mm
Set-up area, length:	2147 mm
Required access area, width:	940 mm
Required access area, height:	1653 mm
Required access area, length:	1910 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body

Nominal pressure (PN):	10
Pressure pipe connection (DN):	65
Pressure pipe connection (OD):	75 mm
Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Inlet nominal size (DN):	160 mm
Inlet nominal size (DN):	150
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Servicing opening:	420 mm

Coverage features

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight

Wastewater contents

Separator contents:	650 l
Total volume:	1350 l
Hose:	700 l
Storage quantity of light liquid:	280 l

Control

Max. permissible switching frequency:	no
---------------------------------------	----