

Grease separator EasyClean free NS 10, Standard, SonicControl



Article information

Item no.: 93010.02 GTIN: 4026092061497 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant Disposal variant: Protection class motor: Sludge bucket: Nominal size (NS): SonicControl: Refill inlet in accordance with DIN 1988: Type of disposal: Load-bearing capacity (DIN 19901):	Standard no no 10 yes no manual with suction hose F3
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
Dimensions Net weight: Gross weight: Set-up area, width: Set-up area, height: Set-up area, length:	195,5 kg 238,5 kg 951 mm 1653 mm 2822 mm



Required access area, width:	951 mm
Required access area, height:	1653 mm
Required access area, length:	2590 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length
	5
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Inlet nominal size (DN):	160 mm
Inlet nominal size (DN):	150
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	9001
Total volume:	1900 l
Hose:	1000 L
Storage quantity of light liquid:	400 l
Control	
Max. permissible switching frequency:	no