

EasyClean round grease separator free, NS 10, Auto Mix

Article information

Item no.: 93010.05/DSP
GTIN:
Price group: 60

Advantages

- Clean and odour-free disposal and cleaning
- Customisation possible through control unit
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. The innovative Shredder-Mix System with integrated macerating system homogenises and circulates the tank contents. Cleaning is carried out via an exterior pump which can be disconnected from the tank by a shut-off valve. A direct disposal pipe socket is available for odour-neutral manual disposal. The fully-automatic program run is controlled by a user-friendly control unit with multi-line display that can be integrated into the building management system via a potential-free contact. Cleaning and disposal can be started remotely using the remote control, which is available as an option. Thanks to the customisable cleaning program with fast-selection function, cleaning can be adapted to the local circumstances as required. Compliance with the German Drinking Water Hygiene Ordinance can be ensured by fully-automatic rinsing of the drinking water pipes. 20 year polyethylene warranty.

Variant

| | |
|------------------------------------|---------------------------|
| Shut-off valve: | yes |
| Disposal variant: | Auto Mix |
| Protection class motor: | yes |
| Sludge bucket: | yes |
| Nominal size (NS): | 10 |
| SonicControl: | no |
| Disposal system: | Disposal connection |
| Type of disposal: | automatic cleaning system |
| Shaft seal: | 2 solenoid valves 1" |
| Load-bearing capacity (DIN 19901): | F3 |

General characteristics

| | |
|--------------------|---|
| Scope of delivery: | Storz-B coupling R 2 1/2" for disposal vehicle connection |
|--------------------|---|

Dimensions

| | |
|----------------------|---------|
| Net weight: | 710 kg |
| Gross weight: | 710 kg |
| Set-up area, length: | 1900 mm |

| | |
|--|---|
| Set-up area, width: | 1690 mm |
| Set-up area, height: | 1910 mm |
| Required access area, length: | 1900 mm |
| Required access area, width: | 1690 mm |
| Required access area, height: | 1910 mm |
| Tank/drain body | |
| Nominal pressure (PN): | 10 |
| Pressure pipe connection (DN): | 65 |
| Pressure pipe connection (OD): | 75 mm |
| Distance pipe bottom outlet to tank bottom: | 1500 mm |
| Distance pipe bottom inlet to tank bottom: | 1570 mm |
| Outlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 200 mm |
| Inlet nominal size (DN): | 160 mm |
| Inlet nominal size (DN): | 150 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Coverage features | |
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Cover locking: | Quick-release closure |
| Tightness: | odour-tight |
| Wastewater contents | |
| Separator contents: | 1500 l |
| Total volume: | 2500 l |
| Hose: | 1000 l |
| Storage quantity of light liquid: | 400 l |
| Pumping device | |
| Pump control: | SPF 300 KE 2.0 |
| Number of pumps: | 2 |
| Connection type: | Direct connection |
| Rated current: | 6,2 A |
| Length of mains cable for pump: | 5 m |
| Self-diagnosis system (SDS): | I |
| Protection class control unit: | IP 55 |
| DSC: | integrated |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Max. pumping capacity: | 60 m ³ /h |
| Max. pumping height: | 17 m |
| Speed: | 2850 U/min |
| Power P1: | 3,6 kW |
| Power P2: | 3 kW |
| Operating mode: | S2 - 30 min. |
| Type of fuse required (electrical protection): | Fuse protection through control unit 400 V |

Type of pump connection cable:
Impeller type:

H07RN-F 7G 1.5 mm²
Radial impeller with macerating system

Control

Control unit:

yes

Motor protection switch:

yes

Type of fuse required (RCD):

30 mA

Protection class probe:

IP 54

Mains frequency:

50 Hz

Operating voltage:

400 V

Connection type:

Direct connection

Potential-free contact:

yes

GSM interface:

no

USB interface:

no

Log book function:

yes

Multi-line display:

yes

Battery buffering:

no

Self-diagnosis system (SDS):

yes

Rated current:

6,2 A