

Grease separator EasyClean free NS 10, Standard, Inspection window, SC



Article information

Item no.: 93010.22 GTIN: 4026092063361 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	
Disposal variant:	Standard
Protection class motor:	no
Sludge bucket:	yes
Nominal size (NS):	10
SonicControl:	yes
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
Dimensions Net weight: Gross weight: Set-up area, width: Set-up area, height:	201,5 kg 244,5 kg 951 mm 1653 mm



Set-up area, length:	2822 mm
Required access area, width:	951 mm
Required access area, height:	1653 mm
Required access area, length:	2590 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length
5 5	5
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Inlet nominal size (DN):	160 mm
Inlet nominal size (DN):	150
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight
5	
Wastewater contents	
Separator contents:	900 l
Total volume:	1900 l
Hose:	1000 l
Storage quantity of light liquid:	400 l
Control	
Max. permissible switching frequency:	no