


Grease separator EasyClean free NS 15, Direct, left





Article information

Item no.: 93015-01-D-L GTIN: 4026092105191

Price group: 60

Advantages

- Inspection window and Refill inlet as standard
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

Variant

Direction of flow:

Shredder-Mix-System:

Inspection window:

Nominal size (NS):

SonicControl:

Refill inlet in accordance with DIN 1988:

Type of disposal:

left

no

yes

yes

manual

General characteristics

Material: PE

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle

connection



Dimensions

Net weight: 360 kg Gross weight: 435 kg Set-up area, length: 3530 mm Set-up area, width: 1490 mm Set-up area, height: 1950 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Nominal pressure (PN): 10 Pressure pipe connection (DN): 65 Pressure pipe connection (OD): 75 mm Distance pipe bottom outlet to tank bottom: 1130 mm Distance pipe bottom inlet to tank bottom: 1200 mm Outlet nominal size (OD): 200 mm Outlet nominal size (DN): 200 mm Inlet nominal size (OD): 200 mm Inlet nominal size (DN): 200 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Servicing opening: 420 mm

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: violet

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents:2230 lTotal volume:3730 lStorage quantity of grease:600 l

Control

Control unit: no