

EasyClean round grease separator free, NS 15, Standard



Article information

Item no.: 93015.05 GTIN: Price group: 60

Advantages

• Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal takes place with the tank open. 20 year polyethylene warranty.

| Variant Disposal variant: Shredder-Mix-System: Sludge bucket: Nominal size (NS): SonicControl: Refill inlet in accordance with DIN 1988: Type of disposal: Load-bearing capacity (DIN 19901): | Standard no no 15,00 no no manual with suction hose F3 |
|---|---|
| General characteristics Material: Standard: Installation situation: Delivery state: | PE EN 1825 free-standing installation Installation-ready (connection parts must be connected on site) |
| Dimensions Set-up area, length: Set-up area, width: Set-up area, height: Required access area, length: Required access area, width: Required access area, height: | 2230 mm 1922 mm 2020 mm 2230 mm 1880 mm 2020 mm |



Tank/drain body Distance pipe bottom outlet to tank bottom: Distance pipe bottom inlet to tank bottom: Outlet nominal size (OD): Outlet nominal size (DN): Inlet nominal size (OD): Inlet nominal size (DN): Connection inlet/outlet sockets:

Coverage features

1550 mm 1620 mm 200 mm 200 mm 200 mm 200 mm PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

| Type of cover: | Cover |
|-----------------------------|-----------------------|
| Cover material: | Polymer |
| Colour of cover: | black |
| Locking: | Quick-release closure |
| Tightness: | odour-tight |
| Wastewater contents | |
| Separator contents: | 2300 l |
| Total volume: | 3800 l |
| Contents of sludge trap: | 1500 l |
| Storage quantity of grease: | 600 l |
| Control | |
| Control unit: | no |
| | |