

Grease separator EasyClean free NS 25, Standard

Article information

Item no.: 93025.01
GTIN:
Price group: 60

Advantages

- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

| | |
|---|--------------------------|
| Disposal variant: | Standard |
| Protection class motor: | no |
| Sludge bucket: | no |
| Nominal size (NS): | 25 |
| SonicControl: | no |
| Refill inlet in accordance with DIN 1988: | no |
| Type of disposal: | manual with suction hose |
| Load-bearing capacity (DIN 19901): | F3 |

General characteristics

| | |
|-------------------------|---|
| Material: | PE |
| Standard: | EN 1825 |
| Installation situation: | free-standing installation |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

Dimensions

| | |
|-------------------------------|---------|
| Diameter: | 630 mm |
| Set-up area, length: | 4760 mm |
| Set-up area, width: | 1350 mm |
| Set-up area, height: | 1555 mm |
| Required access area, length: | 4500 mm |
| Required access area, width: | 1350 mm |
| Required access area, height: | 1525 mm |

Tank/drain body

| | |
|---|---------|
| Distance pipe bottom outlet to tank bottom: | 1030 mm |
| Distance pipe bottom inlet to tank bottom: | 1100 mm |
| Outlet nominal size (OD): | 200 mm |

| | |
|-----------------------------------|---|
| Outlet nominal size (DN): | 200 mm |
| Inlet nominal size (DN): | 200 mm |
| Inlet nominal size (DN): | 200 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Coverage features | |
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Cover locking: | Quick-release closure |
| Tightness: | odour-tight |
| Wastewater contents | |
| Separator contents: | 1200 l |
| Total volume: | 3700 l |
| Hose: | 2500 l |
| Storage quantity of light liquid: | 1000 l |
| Control | |
| Control unit: | no |