

Grease separator EasyClean free NS 40, Standard

Article information

Item no.: 93040.01
GTIN: 4026092103739
Price group: 60

Advantages

- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

| | |
|---|--------------------------|
| Disposal variant: | Standard |
| Shredder-Mix-System: | no |
| Inspection window: | no |
| Nominal size (NS): | 40 |
| SonicControl: | no |
| Refill inlet in accordance with DIN 1988: | no |
| Type of disposal: | manual with suction hose |
| Load-bearing capacity (DIN 19901): | F3 |

General characteristics

| | |
|-------------------------|---|
| Material: | PE |
| Standard: | EN 1825 |
| Installation situation: | free-standing installation |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

Dimensions

| | |
|-------------------------------|---------|
| Gross weight: | 625 kg |
| Set-up area, length: | 6680 mm |
| Set-up area, width: | 1600 mm |
| Set-up area, height: | 1622 mm |
| Required access area, length: | 6200 mm |
| Required access area, width: | 1600 mm |
| Required access area, height: | 1622 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|---|--|
| Distance pipe bottom outlet to tank bottom: | 1130 mm |
| Distance pipe bottom inlet to tank bottom: | 1200 mm |
| Outlet nominal size (OD): | 250 mm |
| Outlet nominal size (DN): | 250 mm |
| Inlet nominal size (OD): | 250 mm |
| Inlet nominal size (DN): | 250 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

Coverage features

| | |
|------------------|-----------------------|
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Locking: | Quick-release closure |
| Tightness: | odour-tight |

Wastewater contents

| | |
|-----------------------------|--------|
| Separator contents: | 5000 l |
| Total volume: | 9000 l |
| Contents of sludge trap: | 4000 l |
| Storage quantity of grease: | 1600 l |

Control

| | |
|---------------|----|
| Control unit: | no |
|---------------|----|