

## Grease separator EasyClean free NS 40, Standard

### Article information

Item no.: 93040.01  
GTIN: 4026092103739  
Price group: 60

### Advantages

- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

#### Variant

|   |                          |
|---|--------------------------|
| Disposal variant:                         | Standard                 |
| Protection class motor:                   | no                       |
| Sludge bucket:                            | no                       |
| Nominal size (NS):                        | 40                       |
| SonicControl:                             | no                       |
| Refill inlet in accordance with DIN 1988: | no                       |
| Type of disposal:                         | manual with suction hose |
| Load-bearing capacity (DIN 19901):        | F3                       |

#### General characteristics

|                         |   |
|-------------------------|---|
| Material:               | PE  |
| Standard:               | EN 1825   |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |

#### Dimensions

|                               |         |
|-------------------------------|---------|
| Set-up area, length:          | 6680 mm |
| Set-up area, width:           | 1600 mm |
| Set-up area, height:          | 1622 mm |
| Required access area, length: | 6200 mm |
| Required access area, width:  | 1600 mm |
| Required access area, height: | 1622 mm |

#### Tank/drain body

|   |         |
|---|---------|
| Distance pipe bottom outlet to tank bottom: | 1130 mm |
| Distance pipe bottom inlet to tank bottom:  | 1200 mm |
| Outlet nominal size (OD):                   | 250 mm  |
| Outlet nominal size (DN):                   | 250 mm  |

|                                   |   |
|-----------------------------------|---|
| Inlet nominal size (DN):          | 250 mm  |
| Inlet nominal size (DN):          | 250 mm  |
| Connection inlet/outlet sockets:  | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Coverage features                 |   |
| Type of cover:                    | Cover   |
| Cover material:                   | Polymer   |
| Colour of cover:                  | black   |
| Cover locking:                    | Quick-release closure   |
| Tightness:                        | odour-tight   |
| Wastewater contents               |   |
| Separator contents:               | 5000 l  |
| Total volume:                     | 9000 l  |
| Hose:                             | 4000 l  |
| Storage quantity of light liquid: | 1600 l  |
| Control                           |   |
| Control unit:                     | no  |