

Grease separator EasyClean free NS 50, Direct

Article information

Item no.: 93050.01/D
GTIN: 4026092103807
Price group: 60

Advantages

- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. 20 year polyethylene warranty.

Variant

Disposal variant:	Direct
Protection class motor:	no
Sludge bucket:	no
Nominal size (NS):	50
SonicControl:	no
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual
Load-bearing capacity (DIN 19901):	F3

General characteristics

Material:	PE
Standard:	EN 1825
Delivery state:	Installation-ready (connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

Dimensions

Set-up area, length:	6680 mm
Set-up area, width:	1800 mm
Set-up area, height:	1882 mm
Required access area, length:	6200 mm
Required access area, width:	1800 mm
Required access area, height:	1882 mm

Tank/drain body

Nominal pressure (PN):	10
Pressure pipe connection (DN):	65
Pressure pipe connection (OD):	75 mm

Distance pipe bottom outlet to tank bottom:	1350 mm
Distance pipe bottom inlet to tank bottom:	1420 mm
Outlet nominal size (OD):	250 mm
Outlet nominal size (DN):	250 mm
Inlet nominal size (DN):	250 mm
Inlet nominal size (DN):	250 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Cover locking:	Quick-release closure
Tightness:	odour-tight

Wastewater contents

Separator contents:	6200 l
Total volume:	11200 l
Hose:	5000 l
Storage quantity of light liquid:	2240 l

Control

Control unit:	no
---------------	----