

## Grease separator EasyClean free Basic, NS 2, Direct, left, Refill inlet



### Article information

Item no.: 94002.12DL  
GTIN: 4026092084328  
Price group: 60

### Advantages

- Odour-reduced disposal with the tank closed
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work. There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

#### Variant

|   |        |
|---|--------|
| Direction of flow:                        | left   |
| Disposal variant:                         | Direct |
| Sludge bucket:                            | no     |
| Nominal size (NS):                        | 2      |
| Refill inlet in accordance with DIN 1988: | yes    |
| Type of disposal:                         | manual |
| Load-bearing capacity (DIN 19901):        | F3     |

#### General characteristics

|                         |   |
|-------------------------|---|
| Material:               | PE  |
| Standard:               | EN 1825   |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |
| Scope of delivery:      | Storz-B coupling R 2 1/2" for disposal vehicle connection       |

#### Dimensions

|                      |          |
|----------------------|----------|
| Net weight:          | 84,5 kg  |
| Gross weight:        | 109,5 kg |
| Set-up area, width:  | 920 mm   |
| Set-up area, height: | 1800 mm  |
| Set-up area, length: | 1560 mm  |

|                               |         |
|-------------------------------|---------|
| Required access area, width:  | 700 mm  |
| Required access area, height: | 1420 mm |
| Required access area, length: | 1560 mm |
| Packaging dimension:          | width   |
| Packaging dimension:          | height  |
| Packaging dimension:          | length  |

|   |   |
|---|---|
| Tank/drain body                             |   |
| Nominal pressure (PN):                      | 10  |
| Pressure pipe connection (DN):              | 65  |
| Pressure pipe connection (OD):              | 75 mm   |
| Distance pipe bottom outlet to tank bottom: | 985 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1055 mm   |
| Outlet nominal size (OD):                   | 110 mm  |
| Outlet nominal size (DN):                   | 100   |
| Inlet nominal size (DN):                    | 110 mm  |
| Inlet nominal size (DN):                    | 100   |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

#### Coverage features

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Cover locking:   | Quick-release closure |
| Tightness:       | odour-tight           |

#### Wastewater contents

|                                   |       |
|-----------------------------------|-------|
| Max. grease layer thickness:      | 120 l |
| Total volume:                     | 660 l |
| Hose:                             | 200 l |
| Storage quantity of light liquid: | 80 l  |