

Grease separator EasyClean free Basic, NS 7, Direct, right, Refill inlet



Article information

Item no.: 94007.12DR
GTIN: 4026092084533
Price group: 60

Advantages

- Odour-reduced disposal with the tank closed
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work. There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

Variant

Direction of flow:	right
Disposal variant:	Direct
Sludge bucket:	no
Nominal size (NS):	7
Refill inlet in accordance with DIN 1988:	yes
Type of disposal:	manual
Load-bearing capacity (DIN 19901):	F3

General characteristics

Material:	PE
Standard:	EN 1825
Installation situation:	free-standing installation
Delivery state:	Installation-ready (connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

Dimensions

Net weight:	154,5 kg
Gross weight:	184,5 kg
Set-up area, width:	1140 mm
Set-up area, height:	2000 mm
Set-up area, length:	1960 mm

Required access area, width:	920 mm
Required access area, height:	1670 mm
Required access area, length:	1960 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body	
Nominal pressure (PN):	10
Pressure pipe connection (DN):	65
Pressure pipe connection (OD):	75 mm
Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Inlet nominal size (DN):	160 mm
Inlet nominal size (DN):	150
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight

Wastewater contents

Max. grease layer thickness:	230 l
Total volume:	1370 l
Hose:	700 l
Storage quantity of light liquid:	280 l