

EasyStarch free starch separator NS 2, Standard

Article information

Item no.: 94202.01

GTIN:

Price group: 60

Description

The separator for starchy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal takes place with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:	Standard
Shredder-Mix-System:	no
Sludge bucket:	yes
Nominal size (NS):	2,00
SonicControl:	no
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3

General characteristics

Installation situation:	free-standing installation
-------------------------	----------------------------

Dimensions

Net weight:	140 kg
Gross weight:	145 kg
Set-up area, length:	2145 mm
Set-up area, width:	940 mm
Set-up area, height:	1655 mm
Required access area, length:	1910 mm
Required access area, width:	940 mm
Required access area, height:	1655 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm

Connection inlet/outlet sockets:

PE-HD pipes in accordance with DIN 19537, HT pipes
in accordance with DIN 19560, PP or AS

Coverage features

Type of cover:

Cover

Cover material:

Polymer

Colour of cover:

violet

Locking:

Quick-release closure

Tightness:

odour-tight

Wastewater contents

Total volume:

1350 l

Control

Control unit:

no