

## EasySink sediment separator free, NS 2



### Article information

Item no.: 97202/000  
 GTIN: 4026092026885  
 Price group: 60

### Advantages

- Waterproof and resistant to aggressive wastewater
- Odour-tight tank
- Low-maintenance operation

### Description

The sediment separator is suitable for exposed installation in frost-protected rooms. The collection tank is equipped with a removable sediment tank (NS 2 with two sediment tanks) both made of permanently resistant polymer (PE). An odour trap is installed in the outlet. An odour-tight cover with quick-release closure makes easy access possible for cleaning and maintenance work. 20 year polyethylene warranty.

#### Variant

Nominal size (NS):

2,00

Type of disposal:

manual with suction hose

#### General characteristics

Material:

PE

Installation situation:

free-standing installation

Delivery state:

Installation-ready (connection parts must be connected on site)

Wastewater-resistant:

resistant to aggressive wastewater

Odour trap:

included

#### Dimensions

Net weight:

50,65 kg

Gross weight:

59,45 kg

Set-up area, length:

985 mm

Set-up area, width:

650 mm

Set-up area, height:

598 mm

Required access area, length:

800 mm

Required access area, width:

650 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

**Tank/drain body**

Distance pipe bottom outlet to tank bottom:	255 mm
Distance pipe bottom inlet to tank bottom:	373 mm
Outlet nominal size (OD):	75 mm
Outlet nominal size (DN):	70 mm
Inlet nominal size (OD):	75 mm
Inlet nominal size (DN):	70 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Volume of collecting tank:	51 l

**Coverage features**

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	630 mm
Length of cover:	630 mm
Locking:	Quick-release closure
Tightness:	odour-tight

**Control**

Control unit:	no
---------------	----