Grease separat. EasyClean Modular ground, NS 2, Standard, D



Article information

Item no.: 98202/00D
GTIN: 4026092027097
Price group: 60

Advantages

- Vertically adjustable upper section with odour-tight cover plates in various load classes
- Waterproof, resistant to aggressive wastewater
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap (NS 4 with separate sludge trap tank) and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	
Sound absorption mat:	modular chamber
Disposal variant:	Standard
Protection class motor:	no
Sludge bucket:	no
Nominal size (NS):	2
SonicControl:	no
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	E4
General characteristics	
Material:	PE
Standard:	DIN 4040-100
Installation situation:	underground installation
Delivery state:	Installation-ready (connection parts must be connected on site)
Dimensions	
Net weight:	190 kg
Gross weight:	190 kg

Groundwater resistant from lower edge of base section:	500 mm
Max. length:	1355 mm
Height tank bottom up to centre section:	750 mm
Height centre section to top edge of tank:	750 mm
Installation depth:	330 - 480 mm
Vertical adjustment:	vertically adjustable upper section, can be tilted by 5 degrees
Required access area, width:	1300 mm
Required access area, length:	1300 mm
Packaging dimension:	width
Packaging dimension:	height
Packaging dimension:	length

Tank/drain body

Distance pipe bottom outlet to tank bottom:	1136 mm
Distance pipe bottom inlet to tank bottom:	1236 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100
Inlet nominal size (DN):	110 mm
Inlet nominal size (DN):	100
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW):	600 mm

Coverage features

Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Width of cover:	659 mm
Height of cover:	121 mm
Length of cover:	659 mm
Cover locking:	locked
Load class:	D 400 (EN 124)
Tightness:	odour-tight and surface water resistant

Wastewater contents

Separator contents:	945 l
Total volume:	1145 l
Hose:	200 l
Storage quantity of light liquid:	80 l

Control

Max. permissible switching frequency:	no