

Grease separator EasyClean free SkimTech Premium, NS 10

Article information

Item no.: 99010.01P
GTIN:
Price group: 60

Description

Variant

Protection class motor: no
Nominal size (NS): 10
Sampling device: yes

General characteristics

Material: PE-HD
Standard: EN 1825
Installation situation: free-standing installation
Delivery state: Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)

Dimensions

Net weight: 480 kg
Operating weight: 2290 kg + 2 * 60 kg (Fässer)
Empty weight: 360 kg
Set-up area, width: 1450 mm
Set-up area, height: 2420 mm
Set-up area, length: 4840 mm
Required access area, width: 960 mm
Required access area, height: 1950 mm
Required access area, length: 3020 mm
Packaging dimension: width
Packaging dimension: height
Packaging dimension: length

Tank/drain body

Distance from centre of outlet pipe to tank bottom: 1200 mm
Distance pipe bottom outlet to tank bottom: 1200 mm
Distance pipe bottom inlet to tank bottom: 1560 mm
Outlet nominal size (DN): 150
Inlet nominal size (DN): 150

Wastewater contents

Separator contents: 1930 l

Working temperature:	0 - 40 °C
Total volume:	1930 l
Pumping device	
Connection type:	Direct connection
Rated current:	0,4 - 0,63 A
Control	
Motor protection switch:	yes
Standby power:	5 W
Type of fuse required (RCD):	30 mA
Protection class probe:	IP 54
Mains frequency:	50 Hz
Operating voltage:	400 V
Connection type:	Direct connection
Potential-free contact:	yes
GSM interface:	yes
USB interface:	yes
Log book function:	yes
Multi-line display:	yes
Battery buffering:	no
Self-diagnosis system (SDS):	yes
Max. permissible switching frequency:	yes
Max. input power:	0,44 kW
Working temperature:	0 - 40 °C