

Grease separator EasyClean free SkimTech Premium, NS 20

Article information

Item no.: 99015.01P

GTIN:

Price group: 60

Description

Variant

Shredder-Mix-System:	no
Nominal size (NS):	15,00
Sampling device:	yes

General characteristics

Material:	PE-HD
Standard:	EN 1825
Installation situation:	free-standing installation
Delivery state:	Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)

Dimensions

Net weight:	645 kg
Operating weight:	3295 kg + 2 * 60 kg (Fässer)
Empty weight:	525 kg
Set-up area, length:	5460 mm
Set-up area, width:	1450 mm
Set-up area, height:	2420 mm
Required access area, length:	3565 mm
Required access area, width:	1160 mm
Required access area, height:	1950 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Distance from centre of outlet pipe to tank bottom:	1130 mm
Distance pipe bottom outlet to tank bottom:	1130 mm
Distance pipe bottom inlet to tank bottom:	1495 mm
Outlet nominal size (DN):	200 mm
Inlet nominal size (DN):	200 mm

Wastewater contents

Separator contents:	2770 l
---------------------	--------

Working temperature:	0 - 40 °C
Total volume:	2770 l
Pumping device	
Connection type:	Direct connection
Rated current:	0,4 - 0,63 A
Control	
Control unit:	yes
Motor protection switch:	yes
Standby power:	5 W
Type of fuse required (RCD):	30 mA
Protection class control unit:	IP 54
Mains frequency:	50 Hz
Operating voltage:	400 V
Connection type:	Direct connection
Potential-free contact:	yes
GSM interface:	yes
USB interface:	yes
Log book function:	yes
Multi-line display:	yes
Battery buffering:	no
Self-diagnosis system (SDS):	yes
Max. input power:	0,44 kW
Working temperature:	0 - 40 °C