

Grease separator EasyClean free SkimTech Premium, NS 20

Article information

Item no.: 99020.01P

GTIN:

Price group: 60

Description

Variant

Protection class motor: no

Nominal size (NS): 20

Sampling device: yes

General characteristics

Material: PE-HD

Standard: EN 1825

Installation situation: free-standing installation

Delivery state: Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)

Dimensions

Net weight: 750 kg

Operating weight: 4240 kg + 2 * 60 kg (Fässer)

Empty weight: 630 kg

Set-up area, width: 1450 mm

Set-up area, height: 2420 mm

Set-up area, length: 6460 mm

Required access area, width: 1160 mm

Required access area, height: 1950 mm

Required access area, length: 4575 mm

Packaging dimension: width

Packaging dimension: height

Packaging dimension: length

Tank/drain body

Distance from centre of outlet pipe to tank bottom: 1130 mm

Distance pipe bottom outlet to tank bottom: 1130 mm

Distance pipe bottom inlet to tank bottom: 1495 mm

Outlet nominal size (DN): 200

Inlet nominal size (DN): 200

Wastewater contents

Separator contents: 3610 l

Working temperature:	0 - 40 °C
Total volume:	3610 l
Pumping device	
Connection type:	Direct connection
Rated current:	0,4 - 0,63 A
Control	
Motor protection switch:	yes
Standby power:	5 W
Type of fuse required (RCD):	30 mA
Protection class probe:	IP 54
Mains frequency:	50 Hz
Operating voltage:	400 V
Connection type:	Direct connection
Potential-free contact:	yes
GSM interface:	yes
USB interface:	yes
Log book function:	yes
Multi-line display:	yes
Battery buffering:	no
Self-diagnosis system (SDS):	yes
Max. permissible switching frequency:	yes
Max. input power:	0,44 kW
Working temperature:	0 - 40 °C