

## EasyOil oil/fuel separator ground, NS 20, Class II, 5800 l, D



### Article information

Item no.: 99620.80DEX

GTIN:

Price group: 60

### Advantages

- Permanent leak tightness up to ground level
- Resistant to and suitable for up to 100 % share of biodiesel
- Suitable for filling stations with high-performance filling pumps, E10 and biodiesel fuels

### Description

The separator for light liquids is suitable for installation in the ground. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and an automatic closure device. One or more surface water resistant covers makes easy access possible for cleaning and maintenance work. A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL. 20 year polyethylene warranty.

#### Variant

Nominal size (NS):	20,00
Type of disposal:	manual with suction hose
Coalescence insert:	no
Load-bearing capacity (DIN 19901):	E4

#### General characteristics

Separator class:	II
------------------	----

#### Dimensions

Net weight:	850 kg
Gross weight:	850 kg
Excess depth:	130 mm
T-DSC:	870
Installation depth:	870 - 1250 mm
Required access area, length:	3110 mm
Required access area, width:	1760 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

**Tank/drain body**

Distance pipe bottom outlet to tank bottom:	1600 mm
Distance pipe bottom inlet to tank bottom:	1630 mm
Outlet nominal size (OD):	200 mm
Outlet nominal size (DN):	200 mm
Inlet nominal size (OD):	200 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS

**Coverage features**

Cover material:	Grey iron
Colour of cover:	black
Load class:	D 400 (EN 124)

**Wastewater contents**

Total volume:	5800 l
Contents of sludge trap:	4000 l
Storage quantity of light liquid:	470 l

**Control**

Control unit:	no
---------------	----