

Coalescence separator EasyOil NS 3, class I, free-standing

Article information

Item no.: 99830R
GTIN: 4026092113622
Price group:

Advantages

- Permanent leak tightness up to top edge of the container
- Resistant to and suitable for up to 100 % share of biodiesel
- Suitable for filling stations with high-performance filling pumps, E10 and biodiesel fuels

Description

The light liquid separator is suitable for free-standing installation in frost-protected rooms and is equipped with a removable coalescence insert. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap (optional) and an automatic closure device. The odour-tight cover enables easy access for cleaning and maintenance work.

An inlet and outlet connection on site is possible with PE-HD pipes according to DIN 19537, PVC-KG pipes according to DIN 19534 and PP or AS on pipe spigots (PE) fitted at the factory. The applicable standards must be observed when selecting the appropriate seals and pipe materials.

20-year polyethylene warranty.

Variant

Nominal size (NS): 3

General characteristics

Material: PE
Standard: EN 858
Installation situation: free-standing installation
Separator class: I

Dimensions

Net weight: 46 kg
Gross weight: 53 kg
Length: 1290 mm
Width: 770 mm
Height: 940 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom: 650 mm
Distance pipe bottom inlet to tank bottom: 670 mm
Outlet nominal size (OD): 110 mm

Outlet nominal size (DN):	110
Inlet nominal size (DN):	110
Coverage features	
Colour of cover:	black
Wastewater contents	
Total volume:	490 l
Contents of sludge trap:	300 l
Storage quantity of light liquid:	70 l